

Claims

1. A preparation delivery device comprising a) a container for the preparation having or being prepared for the arrangement of an opening, b) a mechanism operable to deliver at least part of the preparation in the container through the opening, c) attachment means for
5 connection of the container to the mechanism and d) a sensor system arranged to detect at least one predetermined property of the container or its content, characterized in the improvement comprising

a radiation transmitter arranged to irradiate the container position or a part thereof,
a radiation receiver arranged to receive at least an area part of the radiation from the
10 transmitter after the radiation having been affected by the container position and
the receiver being designed to give an output response representative for the total radiation received from said area part.

2. The device of claim 1, characterized in that at least part of the container is translucent or transparent at the radiation frequency.

15 3. The device of claim 1, characterized in that the container is a cartridge comprising a) a generally cylindrical barrel with a general symmetry axis and having a front end and a rear end, b) an opening or a preparation for an opening at its front end, c) at least one displaceable piston inserted in the barrel between the front end and the rear end.

20 4. The device of claim 3, characterized in that the cartridge is of dual or multi chamber type.

5. The device of claim 1, characterized in that the mechanism includes pump means actuated by electric motor means.

6. The device of claim 1, characterized in that the mechanism includes a control system operable to control at least the electric motor means.

25 7. The device of claim 1, characterized in that the attachment means include movement means operable to move the container in relation to stationary parts of the mechanism.

8. The device of claim 7, characterized in that the movement means include scanning means operable to move the container relative the sensor system.

30 9. The device of claim 8, characterized in that the movement means are also operable to perform an initiation operation on the container.

10. The device of claim 7, characterized in that said movement means are arranged to give a speed of less than 10 cm/sec, preferably less than 1 cm/sec.

11. The device of claim 1, characterized in that the radiation has a wavelength between 300 and 3000 nanometers.

5 12. The device of claim 11, characterized in that the radiation is in the non-visible range.

13. The device of claim 12, characterized in that the radiation is in the infrared range.

10 14. The device of claim 1, characterized in that the transmitter comprises a light emitting diode.

15. The device of claim 1, characterized in that the receiver comprises a photodiode or a phototransistor.

16. The device of claim 15, characterized in that the receiver comprises a daylight filter.

15 17. The device of claim 1, characterized in that the receiver output is non-imaging.

18. The device of claim 1, characterized in that the radiation received is defocused.

20 19. The device of claim 1, characterized in that the irradiation and reception have space angles above 10 degrees.

20. The device of claim 1, characterized in that the transmitter is arranged to give a divergent beam and the receiver is arranged to have a divergent take up angle.

25 21. The device of claim 1, characterized in that transmitter and/or receiver are broadbanded with a preferred frequency variation coefficient of at least plus and minus 1 percent of nominal frequency.

22. The device of claim 1, characterized in that transmitter and receiver are arranged facing in substantially the same direction.

23. The device of claim 1, characterized in that the transmitter and receiver are arranged at a distance from the container.

30 24. The device of claim 1, characterized in that the area covered by the receiver, expressed as the diameter of a circle with corresponding surface, is between 0.5 and 15 mm.

25. The device of claim 1, characterized in that the container has a marking readable by the sensor system.

26. The device of claim 25, characterized in that the marking has more than two discrete levels.

5 27. The device of claim 25, characterized in that the marking has several discrete marking areas.

28. The device of claim 27, characterized in that moving means are present to read the areas in sequence, statically or dynamically.

10 29. The device of claim 25, characterized in that the marking has differences in absorption or reflection.

30. The device of claim 1, characterized in that the relative positioning between sensor and container is adapted to detect a functional property of the container.

15 31. The device of claim 30, characterized in that the functional property is a container contour part, a plunger position, container content or a marking or modification designed to facilitate detection of a functional property.

32. The device of claim 30, characterized in that the relative positioning is adapted to also read a marking on the container, statically or dynamically.

33. The device of claim 1, characterized in that it contains an electronic control unit, preferably a microcontroller.

20 34. The device of claim 33, characterized in that the control unit is operative to receive the modified or unmodified output from the receiver and compare it with one or several memorized characteristics and to act differently if and if not, respectively, a certain similarity is present.

25 35. The device of claim 34, characterized in that the control unit is operative to receive a response versus time function.

36. The device of claim 34 or 35, characterized in that said acting includes the option of activating electric motor means.

37. The device of claim 1, characterized in that the transmitted radiation is modulated.

30 38. The device of claim 1, characterized in that transmitter and receiver are arranged to have a stable axis orientation in relation to their support.

COPIES OF THE REPORT OF THE
COMMISSIONER OF THE GENERAL LAND OFFICE,
IN RESPONSE TO A RESOLUTION PASSED BY THE
HOUSE OF REPRESENTATIVES, JANUARY 18, 1890,
AND A RESOLUTION PASSED BY THE SENATE,
MARCH 1, 1890, RELATIVE TO THE
LANDS BELONGING TO THE UNITED STATES,
AND THE PROCEEDINGS THEREON.

BY ORDER OF THE SECRETARY OF THE INTERIOR,
JAMES H. BECK,

WASHINGTON, D.C.,
JANUARY 1, 1891.

10

15

reflection, transmission, absorption and/or scattering.

20

tainer in relation to stationary parts of the mechanism.

initiation step on the container.

25

~~Went~~
OZ

30 less than 10 cm/sec.

cm/sec.

62. The method of claim 61, characterized in that the reading gives a step difference in the response.

63. The method of claim 58, characterized in providing a marking with differences in absorption or reflection.

64. The method of claim 40, characterized in positioning sensor and container to allow detection of a functional property of the container.

5 65. The method of claim 64, characterized in that the functional property is a container contour part, a plunger position, container content or a marking or modification designed to facilitate detection of a functional property.

66. The method of claim 64, characterized in also reading a marking on the container, statically or dynamically.

10 67. The method of claim 40, characterized in that in the comparing step the characteristic of the received radiation is a response representative for the total radiation received from said area covered.

68. The method of claim 67, characterized in that said establishment of property presence is based on a static response from the receiver.

15 69. The method of claim 67, characterized in that said establishment of property presence is based on a dynamic change from the receiver.

70. The method of claim 69, characterized in that the establishment involves recording a dynamic response versus time function from the receiver.

20 71. The method of claim 70, characterized in that more than one property presence is established.

72. The method of claim 71, characterized in that at least one marking property and one functional property is established.

73. The method of claim 40, characterized in that the transmitted radiation is modulated.

25 74. The method of claim 40, characterized in that the radiation is transmitted and received with stable orientation in relation to stationary parts of the mechanism.

75. The method of any of claims 40 to 74, characterized in that the container is a cartridge comprising a) a generally cylindrical barrel with a general symmetry axis and having a front end and a rear end, b) an opening or a preparation for an opening at its front
30 end, c) at least one displaceable piston inserted in the barrel between the front end and the rear end.

ORIGINAL - TELETYPE

✓ 76. The method of claim 75, characterized in that the cartridge is of dual or multi chamber type.

77. A method for operating a preparation delivery device comprising a) a container for the preparation having, or being prepared for the arrangement of, an opening, b) a mechanism
5 operable to deliver at least part of the preparation in the container through the opening, c) attachment means for connection of the container to the mechanism and d) a sensor system arranged to detect at least one predetermined property of the container or its content, characterized in the improvement comprising

transmitting radiation towards the container position or a part thereof to allow the radiation to be affected by the container position,

receiving at least a part of the affected radiation and

comparing the characteristics of the received radiation with a predetermined characteristic representative for the predetermined property, being a functional property as defined, to establish whether or not the predetermined functional property of the container is present.

15 78. The method of claim 77, characterized in that the received radiation is used to reproduce details from the container position in at least two dimensions providing a representation in the form of pixels in the at least two dimensions.

79. The method of claim 78, characterized in refracting the received radiation to an image on a cathode ray tube or charge coupled device.

20 80. The method of claim 78, characterized in sweeping the container position point by point to produce an image.

81. The method of claim 77, characterized in transmitting and/or receiving a broadbanded radiation with a preferred frequency variation coefficient of at least plus and minus 1 percent of nominal frequency.

25 82. The method of claim 81, characterized in transmitting at least part of the radiation to the content of the container.

83. The method of claim 81, characterized in receiving at least part of the radiation as reflected in substantially the opposite direction as transmission.

84. The method of claim 77, characterized in that the functional property is a
30 container contour or a plunger position.

85. The method of claim 77, characterized in any of the characteristics of claims 41 to 86.

TECHNICAL

86. A system of marked medical containers comprising a) at least two containers having different properties in at least one respect and b) at least one machine readable marking difference on each of said containers, the marking being designed to allow discrimination between said differences in properties, characterized in the improvement comprising

5 ing

that the marking provides said difference by having at least one area with different absorbance or reflectance when irradiated with radiation in non-visible frequency ranges.

87. The system of claim 86, characterized in that the marking has more than two discrete levels.

10 88. The system of claim 86, characterized in that the marking has several discrete marking areas.

89. The system of claim 87, characterized in that the areas provide step level changes when read in sequence, statically or dynamically.

15 90. The system of claim 86, characterized in that the marking has differences in absorption or reflection.

91. The system of claim 86, characterized in that the markings provide an alteration in radiation frequency distribution.

92. The system of claim 86, characterized in that the marking has an opaque or reflecting backing.

20 93. The system of claim 86, characterized in that the areas have a size, expressed as the diameter of a circle with corresponding surface, of at least 1 mm, preferably at least 2 mm and most preferably at least 5 mm

94. The system of claim 86, characterized in that the containers have similar functional properties in at least one respect.

25 95. The system of claim 94, characterized in that the containers are similar in the respect that they are adapted to be used in the same medical delivery device.

96. The system of claim 94, characterized in that the containers are similar in that they contain at least one common medical compound.

30 97. The system of claim 86, characterized in that the difference in property comprises a difference in content medical compounds, content volume or content concentration.

FILED IN: 12 FEB 1980

98. A syringe cartridge type container, for use with a preparation delivery device, comprising a) a generally cylindrical barrel with a general symmetry axis and having a front end and a rear end, b) an opening or a preparation for an opening at its front end, c) at least one displaceable piston inserted in the barrel between the front end and the rear end and d) a machine readable marking on the container, characterized in the improvement comprising

that the marking includes at least one marking area with detectable absorbency or reflectance when irradiated with radiation in non-visible frequency ranges,

that the piston has at least one surface part with detectable absorbency or reflectance when irradiated with radiation in non-visible frequency ranges and that said piston surface part is exposed or exposable to the radiation through at least a part of the barrel and

that at least a part of said marking area and said piston surface part are located at the same position along the barrel symmetry axis.

99. The cartridge of claim 98, characterized in that at least a part along the barrel axis is free from marking allowing exposure of the piston.

100. The cartridge of claim 98, characterized in that in addition to the marking area covering the piston position at least one further marking area with different absorbency or reflectance is arranged along the barrel axis.

101. The cartridge of claim 98, characterized in that the cartridge is of dual or multi chamber type having more than one piston.

102. A machine readable marking system comprising at least two discrete areas of different detectable absorbencies when irradiated individually and providing a number of information carrying combination possibilities when read in predetermined sequence, characterized in the improvement comprising

that each area comprises more than two discrete levels of absorbencies.

103. The system of claim 102, characterized in that the marking has several discrete marking areas.

104. The device of claim 103, characterized in that moving means are present to read the areas in sequence, statically or dynamically.

105. The device of claim 102, characterized in that the marking has differences in absorption or reflection.

5 that the transmitter is arranged to irradiate the object with non-imaging radiation,
 that the receiver is arranged to collect non-imaging radiation affected by an area part
 of the object and

10 107. ~~The~~ device of claim 106, characterized in any characteristic of claims 2
to 39.

100 a3